Eliane S/A Revestimentos Cerâmicos

Rua Maximiliano Gaidzinski 245 88845-000 Cocal do Sul - SC - Brasil Tel + 55 48 3447 7981 Fax + 55 48 3447 7706 www.eliane.com



# TECHNICAL CHARACTERISTICS OF PRODUCT

The characteristics of the product specified in this technical report meet the specification and test methods according to norm ANSI A 137, ASTM, DIN 51130 and AS 4586 requirements.

## **PRODUCT SPECIFICATION**

| Reference                | MUNARI GRAFITI AC 29X59 |
|--------------------------|-------------------------|
| Product Code             | 8032803                 |
| Nomimal Size (N)         | 29 cm x 59 cm           |
| Work Size (W)            | 290,0 mm x 590,0 mm     |
| Thickness                | 9,0 mm                  |
| Water Absorption         | Bla (≤0,50%)            |
| Shade Variation          | V2                      |
| Application Joint        | 2,0 mm                  |
| Coverage Area            | 1,20 m²/cx              |
| Number of pieces per box | 7                       |
| Usage Recommendation     | LC                      |

Check if the product is adequate for the planned installation area according to the room application table:

| CODE | APPLICATION ROOM   |  |
|------|--|--|
| LA   | Residendial bathrooms.   |  |
| LB   | Residential areas, bedrooms and kitchens with no access to the street and LA spaces.   |  |
| LC   | Commercial areas without access to the street, garages, porches and residential areas with access to the street, and LB and LA spaces. |  |
| LD   | Commercial areas with access to the street and LA, LB, and LA spaces.  |  |
| LE   | Sidewalks and outside flat areas and LD, LC, LB and LA spaces.   |  |
| LP   | Pools.   |  |
| LF   | Facades.   |  |

| PHYSICAL PROPERTIES         |       |  |
|-----------------------------|-------|--|
| Breaking strength (lbf)     | ≥ 250 |  |
| Water Absorption (%)        | ≤ 0,5 |  |
| Visible abrasion Resistance | 2     |  |

Eliane S/A Revestimentos Cerâmicos

Rua Maximiliano Gaidzinski 245 88845-000 Cocal do Sul - SC - Brasil Tel + 55 48 3447 7981 Fax + 55 48 3447 7706 www.eliane.com



|                 | ANTISLIP CLASSIFICATIONS |  |  |
|-----------------|--------------------------|--|--|
| Angle:          | Oil: 0°                  |  |  |
|                 | Dry: 19°                 |  |  |
| Classification: | Unclassified             |  |  |

Test method according to norm DIN 51130 (R)

### SLIP RESISTANCE CLASSIFICATION – METHOD PENDULUM TEST

Test method according to norm AS 4586 – Anexo A.

### **CHEMICAL PROPERTIES**

| Chemical Resistance | Class C |
|---------------------|---------|
| Stain Resistance    | Class A |

#### Attention:

- Sand may produce scratches on any type of surface covering (stone, wood, vinyl or ceramic tiles).
  Therefore, ceramic tiles are not warranted against scratches, especially concerning glossy surface products.
- Special care is recommended during the application and its use
- In residential areas, we recommend to protect the base of furniture and appliances.
- Product manufactured by the wet process.
- Product with Class I combustibility, according to NBR 15575.

May 02, 2017. Cocal do Sul – SC – Brazil

rgn

Sergio Pereira Ruzza Gerente de Tecnologia Cerâmica

Angela Waterkemper Vieira Analista Desenvolvimento de Processos